IP Link® Device Interface
Ethernet Communication Sheet

This document provides additional assistance with wiring your Extron IP Link enabled product to your device. Different components may require a different wiring scheme than those listed below.

For complete operating instructions, refer to the user's manual for the specific Extron IP Link enabled product or the controlled device manufacturer supplied documentation.

Device Specifications:

Device Type:	Display
Manufacturer:	Samsung
Firmware Version:	N/A
Model(s):	UN40ES6500F

Minimum Software and Firmware Requirements:

IP Link Compiler	IP Link Firmware	GC Version
1.6.0	1.16	3.5.0

Version History:

Driver Version	Date	Notes
1	6/11/2013	Initial version.

Driver Notes:

Control Commands & States:

Aspect Ratio	16:9 4:3	Zoom 1	Zoom 2
Channel	Up	Down	
Input	TV HDMI1	AV HDMI2	Component HDMI3
Mute	Toggle		
Power Control	On	Off	
Volume (Discrete)	0 to 100 in steps of 1		
Volume (Step)	Up	Down	

Status Available:

N/A

Network communication:

When configuring the Ethernet driver, be sure device settings match that of the GC configuration.

Port Type:	Ethernet
Logon Credentials Supported:	Undetermined
Default Port:	1515
Multi-Connection Capable:	Undetermined
Port Changeable:	Yes

Ethernet Driver Configuration Description:

Please refer to user manual for settings and changes to the network communication parameters.

Notes for the Device: